



# Trimble T100

TABLET



Depend on it.

## KEY FEATURES

- ▶ Fast and powerful processor, for efficient data collection and data processing
- ▶ Windows® 10 brings the office to the field
- ▶ Large 10.1-inch touchscreen, sunlight readable and wet weather efficient with a high resolution display
- ▶ Ergonomic design that's comfortable and portable on long demanding days in the field
- ▶ Expandable Trimble® Empower modules, provide flexibility for user configurations

Learn more: [geospatial.trimble.com/trimble-t100-tablet](https://geospatial.trimble.com/trimble-t100-tablet)

# Trimble T100 TABLET

| PRODUCT MODELS       | T100 (WI-FI) | T100 (4G LTE) |
|----------------------|--------------|---------------|
| WLAN (Wi-Fi)         | Yes          | Yes           |
| 4G Data              | No           | Yes           |
| Memory storage (SSD) | 512 GB       | 512 GB        |
| Internal GNSS        | Included     | Included      |

## STANDARD FEATURES

### System

- Intel® 8th Generation Core™ i5 Processor
- Intel HD Graphics 620
- 16 GB RAM
- 512 GB Storage<sup>1</sup>
- 10.1" 800 nits 1920 x 1200 (16:10) LED-backlight screen with capacitive multi-touch
- Wacom Digitizer for EMR Pen Support
- 8 Megapixel with LED Flash rear camera
- Wi-Fi 802.11ac
- Bluetooth® v 5.1
- 4G LTE WWAN EM7565
- Internal battery 92 Wh non removable
- Integrated speaker and microphone
- IP65 Dust and Moisture Ingress Protection

### Operating System

- Microsoft® Windows® 10 Professional

### Communications

- Cellular: 4G LTE worldwide coverage, certified on Verizon and AT&T, data only
- Wi-Fi 802.11ac
- Bluetooth v 5.1
- USB 3.1 Type C x 2
- Supports USB C DisplayPort Alt Mode

### Standard Accessories

- EMR Stylus with replacement tips and removal tool
- AC-DC power adapter with power cord
- Screen protector
- USB A to USB C adapter

### Optional Accessories

- EMR Stylus and replacement tips and removal tool
- Handstrap
- Vehicle Power Supply
- Office stand
- Pole mount (Short and long versions)

- 1 Total usable memory will be less depending upon actual system configuration.
- 2 Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other settings or preferences.
- 3 Tested under MIL-STD-810H method 501.6, Procedure II, and method 502.6, Procedure II. Battery capacity is reduced at lower temperatures or extremely high temperatures. Batteries should neither be charged at temperatures below 32 °F (0 °C) nor temperatures above 113 °F (+45 °C) to avoid impacting battery longevity and performance.
- 4 SBAS (Satellite Based Augmentation System), where available.

Caution: Do not expose bare skin to this product when handling this unit in extreme hot or cold environments. Do not charge batteries in extreme hot environments

Specifications subject to change without notice.

## TECHNICAL SPECIFICATIONS

### Physical

Size ..... 279 mm x 200 mm x 18.5 mm (11 in x 7.9 in x 0.7 in)  
 Weight ..... 1.65 kg (3.6 lbs.)  
 Processor ..... Intel® Core™ i5  
 Memory ..... 16 GB SDRAM  
 Storage: 512 GB SSD

User Interface ..... Power button, directional pad, programmable function keys  
 Power / Battery Status LED, On screen keyboard

Battery ..... 92 Wh internal non removable  
 Battery life ..... 10 hours @ 20 °C with GPS on  
 Charging time ..... 1:15 to 50% 3 hours to 100%<sup>2</sup>

### Environmental

Temperature  
 Operating ..... -20 °C to +55 °C (-4 °F to 131 °F)<sup>3</sup>  
 MIL STD 810H Method 501.7, 502.7 Procedure II

Storage ..... -40 °C to +70 °C (-40 °F to 158 °F)  
 MIL STD 810H Method 501.7, 502.7 Procedure I

Thermal Shock ..... -20 °C and 60 °C non-operating  
 MIL STD 810H Method 503.7 Procedure I-C

Humidity ..... 0% – 95% non-condensing  
 MIL STD 810H Method 507.6 Procedure II - Aggravated Cycle

Water & dust proof ..... IEC 60629 Edition 2 - IP65

Vibration / Shock resistance ..... MIL STD 810H Method 514.8 Procedure I  
 - Random Vibration  
 MIL STD 810H Method 514.8 Procedure II - Loose Cargo Transportation

Drop ..... Tests include room temperature, -20 °C, +60 °C  
 MIL STD 810H Method 516.8 Procedure IV - Transit Drop

Chemical Exposure ..... Contamination by Fluids  
 MIL STD 810H Method 504.3 Procedure II

Non Operating Altitude ..... -30 °C and 12,192 m (40,000 Feet)  
 MIL STD 810H Method 500.6 Procedure I

Operating Altitude ..... 5 °C and 9,144 m (30,000 Feet)  
 MIL STD 810H Method 500.6 Procedure II

### Input/Output

Display ..... LED backlight scratch-resistant, auto rotate  
 Size ..... 10.1" capacitive multi-touch with EMR  
 Resolution ..... 1920 x 1200 px  
 Brightness ..... 800 nits

Audio ..... Built-in microphone and speaker  
 I/O ..... USB 3.1 type c x 2  
 Trimble EMPOWER Module Bays x 2

AC / DC Adapter ..... AC 100–240 V, 50–60 Hz,  
 DC 5 V, 9 V, 15 V, 20 V, 65 W  
 USB C PD 65W

Digital camera (rear facing) ..... 8 MP with flash

Sensors ..... E-Compass, Accelerometer, gyroscope,  
 ambient light sensor, proximity sensor

### GNSS

Internal antenna ..... Beidou, Galileo, GLONASS, GPS L1 C/A, QZSS



Contact your local Trimble Authorised Distribution Partner for more information

**NORTH AMERICA**  
 Trimble Inc.  
 10368 Westmoor Dr  
 Westminster CO 80021  
 USA

**EUROPE**  
 Trimble Germany GmbH  
 Am Prime Parc 11  
 65479 Raunheim  
 GERMANY

**ASIA-PACIFIC**  
 Trimble Navigation  
 Singapore PTE Limited  
 3 HarbourFront Place  
 #13-02 HarbourFront Tower Two  
 Singapore 099254  
 SINGAPORE

